

EIP-WX5000

Widescreen 3 DLP® Projector
5200 ANSI Lumens

Get the film-like imaging of DLP® technology in a projector with conference room brightness and built-in network control.

- ▼ 5200 ANSI Lumens bright, at 90% uniformity, and a 1800:1 contrast ratio.
- ▼ WXGA (16:10) resolution. UXGA~VGA, MAC and Workstation compatible.
- ▼ 3 DLP™ imaging technology delivers a “seamless” high contrast image.
- ▼ Power Zoom and Focus Lens. Optional Wideangle and Telephoto lenses.
- ▼ Horizontal & Vertical Lens Shift. H, V & Geometric Keystone Correction.
- ▼ Dual Lamp System provides redundancy and permits 4 brightness levels.
- ▼ Wireless/wired remote. Wireless remote mouse. Mechanical shutter.
- ▼ RS-232 System and Network Control Compatible: Built in D-sub 9 and RJ45.
- ▼ Smart data compression/expansion, and video scaling. sRGB Compatibility.
- ▼ Displays both Regular 4:3 and Widescreen 16:9 ratio video formats.
- ▼ Converts Interlace video to Progressive scan. 2-3 Pulldown Support.
- ▼ Accepts Analog and Digital Video input signals up to 1080p.
- ▼ Power Management, Keylock Security, and Custom Warmup Screen options.
- ▼ Unique Projector Stack Control and VideoWall Signal Division features.
- ▼ 3 Year* Projector Warranty!




EIKI
Projectors... and more!

EIP-WX5000 5200 ANSI Lumens

SPECIFICATIONS:

Screen Brightness	up to 5200 ANSI Lumens
Illumination Uniformity	90%
Color Reproduction	8-bit/16.7 Million Colors
Contrast Ratio	1800:1
Horizontal Resolution	550 TV Lines (HDTV)
Projection Lamp	280 Watt UHP x 2
Estimated Lamp Life	up to 3000 Hours of Use
Imaging System	0.65" DDR 3 DLP® DMD®
Screen Pixels	1,024,000 (1280 x 800) in stripe configuration
Lens Type	Power Zoom and Focus
Lens Specs	Speed: f:2.5; FL: 1.00~1.26 in. (25.5~32.0 mm)
Lens Ratios	Zoom Max:Min: 1.25:1; Throw:Width: 1.8~2.5:1
Image Diagonal	60~280 in. (152.4~711.2 cm)
Image Width	4.2~19.8 ft. (1.3~6.03 m)
Throw Distance	7.9~45 ft. (2.4~13.7 m)
Front Elevation/Maximum Pitch	up to 5° up/9° off the horizontal
Vertical Anti Keystone	Power Lens Shift (Top:Bottom) +/- 66%
Horizontal Anti Keystone	Power Lens Shift (L:R~R:L) +/- 35%
Vertical Keystone Correction	Digital: up-to 40° up or down
Horizontal Keystone Correction	Digital: up-to 30° left or right
Geometric Keystone Correction	Digital
Scanning Frequency	Auto: H Sync. 15-126 kHz; V Sync. 43~200 Hz
Dot Clock	12~230 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control/Power Management	Full Function/Auto Shut-Off
Remote Projector Control (with Mouse)	Wireless/Wired x 1
Wired Remote Port	MiniStereo x 1
RS-232 Port	D-sub 9 x 1
LAN Port	(10Base-T/100BaseTX) RJ45 x 1
Computer Native Resolution	1280 x 800 (WXGA)
Computer: Compatibility	UXGA, SXGA+, SXGA, WXGA XGA, SVGA, VGA, MAC & Workstation
Computer: Formats	1600 x 1200 through 640 x 480
Computer: Image Sizing	Normal, or Smart Compressed or Expanded
Video: Color Systems	NTSC/PAL/SECAM/NTSC4.43/PAL-M/N
Video: Aspect Ratios Supported	4:3 and 16:9
Video: Image Resizing	Video Scaling Technology
Video: Resolutions Supported	
SDTV (Composite, S-Video, Component)	480i, 540p, 576i
EDTV (DVI w/HDCP)	480p, 576p
HDTV (DVI w/HDCP)	720p/60, 1035i/60, 1080i/50/60, 1080p/50/60
Signal Inputs:	
HDMI	HDMI x 1
DVI-D(w/HDCP)	DVI-D x 1
plus Audio: Stereo:	MiniStereo x 1
Computer/Component 1:	D-sub 15 x 1
plus Audio: Stereo:	MiniStereo x 1
Computer/Component 2:	BNC x 5
plus Audio: Stereo:	MiniStereo x 1
S-Video	S-Video x 1
plus Audio: Stereo:	MiniStereo x 1
Composite	RCA x 1
plus Audio: Stereo:	MiniStereo x 1
Outputs:	
Computer/Component	D-sub 15 x 1
Audio: Line	Stereo: MiniStereo x 1
Audio: Amplifier	Stereo: 3 Watts
Audio: Built In Speakers	Stereo: 1.3 x 2.6 in. (3.4 x 6.8 cm) (oval) x 2
Fan Noise	as low as 34 dBA
Cabinet Size (HxWxD)	7.5 x 19.7 x 25.1 in. (190 x 500 x 637 mm)
Weight	58.6 lbs. (26.6 kg)
Packaged Size (HxWxD)	15.8 x 28.4 x 34.3 in. (400 x 720 x 870 mm)
Packaged Weight	77.2 lbs. (35 kg)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption:	up to 755 W
Heat:	up to 2,578 BTU/hr (649 Kcal/hr)
Power Cord	6.0' (1.8M) Type 3, Detachable
Electrical Safety Compliance	UL, cUL, IEC
Electromagnetic Compatibility	FCC Part 15 Class A, CE Mark
Security Facilities	Kensington® Security Slot
Operating Temperature	41~104°F (5~40°C)
User Maintenance	Clean Air Filter, Replace Lamps
Warranty: (to the original end-use customer)	
Projector:	3 Years/6000 Hour Use* (Parts/Labor to Correct Defects)
Lamp:	90 days (Failed Lamp Replaced Pro-Rata) *whichever occurs first




INCLUDED ACCESSORIES:

Printed Quick Setup Guide and Owner's Manual. Quick Setup Guide, Owner's Manual and CAD Drawings on CD ROM. 6.0 ft. (1.8M) AC Power Cord. Lens Cover. VGA-type Computer Input Cable (D-sub 15). Wireless/wired Remote with Mouse Control & 2 x AA batteries. Remote Mouse Receiver on 5.25 ft. (1.6M) USB-A cable.

OPTIONAL ACCESSORIES:

Replacement Lamps. Wideangle and Telephoto Lenses. ATA-Style Shipping Case with Wheels and Telescoping Handle. Ceiling Mount. Ceiling Post and Plate.

Talk to your EIKI Dealer... the "pro" in projectors.



Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130

Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St. Unit 2, P.O. Box 156, Midland, ON L4R 4K8

Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>

EIKI

Projectors... and more!

Specifications subject to change without notice.

©2008 EIKI International, Inc. Printed in the USA. 08/15/08